HYSTEC
THE SAFETY COMPANY

Catalogue

SCBA series

Self-Contained Breathing Apparatus

LimpahMas

HEAD OFFICE
+6221 3455 953
Jl. Lautze No. 20A
Jakarta Pusat 10710

JAKARTA - LINDETEVES TRADE CENTER
Jl. Hayam Wuruk No. 127
Jakarta Barat 11180
Lantai GF1 Blok A2 No. 45-46
+6221 6220 1632, 6220 1639

Lantai GF1 Blok B7 No. 2-3
+6221 6230 5540, 6230 5541

Lantai GF1 Blok A11 No. 2-3
+6221 6220 0745, 6220 0746

JAKARTA - KARANG ANYAR
Jl. Lautze No. 20A Jakarta Barat 10710
+6221 3890 0980

SURABAYA - RADEN SALEH
Jl. Raden Saleh No. 16, Jawa Timur
+6231 9924 5008, 9924 5046

WHATSAPP CUSTOMER SERVICE
+62 815-1017-1509

limpahmasindonesia
www.limpahmas.com
limpahmasindonesia



Features:

- The streamlined back-plate frame provides a comfortable fit with a lower profile
- Better designed shoulder straps to dispersive and reduce the user burden, aslo with ease of donning and doffing
- Equipted with sFP or cFP facepiece, plus pressure demand regulator with First
- Breath Activation and low exhalation resistance for easy breathing and reduced user fatigue
- Fluorescent gauge and whistle end-of-service alarm be combined into one assembly for the ease of use

Components	Specifications
Full Face Mask	Silicon
Back Plate Assembly	Flame retardant (Nomex / Kevlar is available)
Cylinder Valve	90°C self-lock w/guage w/hand wheel
Air Cylinder	6.8L Composite (9.0L Composite is available)
Alarm volume	> 90 dBA
Working Pressure	300Bar
Alarm activation	55±5Bar
Weight(without air cylinder)	4.5KG
Exhalation Resistance	1000Pa
Inhalation Resistance	500Pa
Approved temperature	-30°C to +60°C
Nominal Duration	45-60minutes
Approvals	MED 96/98/EC/ EN137: 2006 / EN 136:1998+AC:2003

As the general use in industrial air breathing apparatus which is designed with flexible,reliable and serviceable. It usually be applied to marine, chemical, oil/gas industry etc., for the complex performance;

1 SET / CASE / CARTON



HYSTEC
THE SAFETY COMPANY